

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 November 2005 (10.11.2005)

PCT

(10) International Publication Number
WO 2005/106228 A1

(51) International Patent Classification⁷: **F02D 41/20**,
41/40

[JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA,
1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(21) International Application Number:
PCT/JP2005/005616

(74) Agents: **KAWAGUCHI**, Yoshiyuki et al.; Acropolis 21
Building 6th floor, 4-10, Higashi Nihonbashi 3-chome,
Chuo-ku, Tokyo 1030004 (JP).

(22) International Filing Date: 18 March 2005 (18.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-131462 27 April 2004 (27.04.2004) JP

(71) Applicant (for all designated States except US): **TOY-
OTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toy-
ota-cho, Toyota-shi, Aichi, 4718571 (JP).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **YOSHIZAKI**, Kouji

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: EIGHT-CYLINDER ENGINE



(57) Abstract: Even in a construction in which fuel injection valves for eight cylinders are energized by two EDUs, a sufficient charging time for each EDU can be ensured. In an eight-cylinder engine including fuel injection valves provided one for each cylinder of the eight-cylinder engine for injecting fuel thereinto, a first valve drive unit for driving four of the eight fuel injection valves to open and close by energizing these four fuel injection valves; and a second valve drive unit for driving four fuel injection valves other than the first-mentioned four fuel injection valves to open and close by energizing the second-mentioned four fuel injection valves, both of the valve drive units drive those fuel injection valves which are provided on cylinders for which combustion and expansion strokes occur at equal intervals. For example, the first valve drive unit (12) energizes those fuel injection valves which are provided on a first cylinder, a fourth cylinder, a sixth cylinder, and a seventh cylinder, and the second valve drive unit (13) energizes those fuel injection valves which are provided on a second cylinder, a third cylinder, a fifth cylinder, and an eighth cylinder.

WO 2005/106228 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*